



Non-Latex • Powder-Free • Textured





Sempermed is a vertically integrated manufacturer that provides focused sales, marketing, and logistical support to those in need of hand protection.







We've delivered the right combination of fit, feel, tactile sensitivity, strength and value in a latex-free exam glove. With Tender Touch[™] gloves, you can feel a baby's pulse, experience comfort, and have the strength and protection you need. Your hands will feel safe and secure when working with even the most delicate items.

With comfort and fit comes safety and peace of mind...

FEATURES

- Excellent barrier and chemical resistance
- Manufactured without natural rubber
- Powder-Free
- Packing configuration provides 200 gloves per box instead of the normal 100

BENEFITS

- Enhanced protection
- Eliminates exposure to latex
- Eliminates aerosolization of glove powder
- Greater operational efficiencies that provide value to your organization

GLOVE COUNT (By Weight)

200 Gloves/Box (180 gloves XL) 10 Boxes/Case

THICKNESS* (Single Wall)

 Finger:
 0.05 mm/2.0 mils min.

 Palm:
 0.05 mm/2.0 mils min.

PHYSICAL PROPERTIES*

Before aging:

Tensile Strength: 14 MPa min. Elongation: 500% min.

*The specifications provided reflect the minimum acceptable requirements of ASTM and FDA where applicable. Gloves offered by Sempermed USA, Inc. meet or exceed these physical requirements. Independent laboratory test results are available upon request.

All Sempermed gloves are single use only.

PRODUCT CHARACTERISTICS

- Synthetic Nitrile Rubber (NBR)
- Textured Fingertips
- Powder-Free
- Ambidextrous
- Beaded Cuff
- Single Use Only

Order #	Size	Length (min.)	Palm Width (avg.)
TTNF201	XS	220mm	70mm +/- 10mm
TTNF202	S	220mm	80mm +/- 10mm
TTNF203	М	230mm	95mm +/- 10mm
TTNF204	L	230mm	110mm +/- 10mm
TTNF205	XL	230mm	120mm +/- 10mm

Sempermed[®]S

We are people protection.™

www.SempermedUSA.com • 13900 49th Street North • Clearwater, FL 33762 Phone: 1.800.366.9545 • Fax: 1.800.763.5491 Outside the U.S.: 727.787.7250 • Fax: 727.787.7558

